

CLAIMS

1. A method for routing messages comprising: converting a message received from a sender into an internal format comprising at least an attribute part and a data  
5 part, writing into said attribute part data extracted from said received message; and routing said converted message in dependence on the data in said attribute part.
2. The method of claim 1, comprising identifying the format in which the message was received, and writing data identifying that format into said attribute part.  
10
3. The method of claim 1, comprising determining where to send the message in dependence on the attributes.
4. The method of claim 1, comprising authenticating the identity of the sender of  
15 the message.
5. The method of claim 1, comprising identifying a set of services to which the message is addressed.
- 20 6. The method of claim 4, comprising determining whether the sender is authorised to access at least one service; and,  
in dependence on the result of said authorisation determination, sending the converted message to the identified service.
- 25 7. The method of claim 6, in which said identified service updates the data held in the attribute part of the message.
8. The method of claim 6, comprising storing a plurality of routing rules and in which determining whether the sender is authorised to access at least one service  
30 comprises comparing said plurality of routing rules with the attributes of a converted message.

0904184-082104

9. The method of claim 1, wherein said received message comprises a digital signature, the method comprising verifying the signature.

10. The method of claim 9, comprising writing into said attribute part data  
5 identifying the received digital signature.

11. The method of claim 1, comprising storing a plurality of routing rules; comparing the attributes of a converted message with the routing rules; and routing said converted message in dependence on said comparison.

10

12. The method of claim 1 comprising searching for a transaction identifier in the received message.

13. The method of claim 12, comprising allocating a new transaction identifier if  
15 no transaction identifier is detected in the received message.

14. The method of claim 12, comprising, if a transaction identifier is detected, searching for data identifying the status of a transaction by reference to the detected transaction identifier.

20

15. A program element comprising program code for configuring a computer system to route a message, the program code operable to:

convert a message received from a sender into an internal format comprising at least an attribute part and a data part;

25 write into said attribute part data extracted from said received message; and route said converted message in dependence on the data in said attribute part.

16. A program element comprising program code translatable to configure a computer system to route a message, the program code operable to:

30 convert a message received from a sender into an internal format comprising at least an attribute part and a data part;

write into said attribute part data extracted from said received message; and

route said converted message in dependence on the data in said attribute part.

17. A computer-readable medium encoded with computer-readable program code for configuring a computer system to route a message, the program code operable to:

5 convert a message received from a sender into an internal format comprising at least an attribute part and a data part;

write into said attribute part data extracted from said received message; and

route said converted message in dependence on the data in said attribute part.

10 18. A computer-readable medium encoded with computer-readable program code translatable to configure a computer system to route a message, the program code operable to:

convert a message received from a sender into an internal format comprising at least an attribute part and a data part;

15 write into said attribute part data extracted from said received message; and route said converted message in dependence on the data in said attribute part.

19. A computer system for routing messages to one or more services comprising:

20 a parser for converting a message received from a sender into an internal format comprising an attribute part and a data part, said attribute part containing data extracted from the received message; and

a router for routing the converted message in dependence on the data in said attribute part.

25 20. The computer system of claim 19, in which said parser is configured to identify the format in which the message was received, and to write data identifying that format into said attribute part.

30 21. The computer system of claim 19, in which said router is configured to determine where to send the message in dependence on the attributes.

09034104 092104  
TOT 260 45 14650

22. The computer system of claim 19, in which said the router is configured to authenticate the identity of the sender of the message.

23. The computer system of claim 19, in which said router is configured to identify  
5 a set of services to which the message is addressed.

24. The computer system of claim 19, in which said router is configured to:  
identify at least one service to which the message should be sent;  
determine whether the sender is authorised to access said identified service;  
10 and,  
in dependence on the result of said authorisation determination, selectively  
send the converted message to the identified service.

25. The computer system of claim 19, said router being configured to store a  
15 plurality of routing rules and to determine whether the sender is authorised to access a  
service by applying said rules to the attributes of a converted message.

26. The computer system of claim 19, wherein said parser is configured to verify  
signatures included in said received messages.  
20

27. The computer system of claim 19, said parser comprising a plurality of  
applications for converting said received message, said parser selecting at least one of  
said applications in dependence on the data extracted from said received message.

28. The computer system of claim 27, wherein said data extracted from said  
25 received message includes a message type, said parser selecting at least one of said  
applications in dependence on the type of a message.

29. The computer system of claim 27, wherein said data extracted from said  
30 received message includes protocol data, and said parser selects at least one of said  
applications in dependence on the protocol(s) under which the message was received.

31. The computer system of claim 30, configured to allocate a new transaction  
5 identifier if no transaction identifier is detected in the received message.

10 33. A computer system configured to provide a plurality of protocol handlers each configured to extract protocol data from a message received in a particular format.

35. A computer system according to claim 33 configured to select a protocol handler in dependence on the type of data in the received message.

37. A computer program for routing messages, said program comprising computer  
25 executable instructions for converting a message received from a sender into an  
internal format comprising at least an attribute part and a data part, writing into said  
attribute part data extracted from said received message; and routing said converted  
message in dependence on the data in said attribute part.

30 38. The computer program of claim 37, comprising computer executable instructions for identifying the format in which the message was received, and writing data identifying that format into said attribute part.

39. The computer program of claim 37, comprising computer executable instructions for determining where to send the message in dependence on the attributes.

5

40. The computer program of claim 37, comprising computer executable instructions for authenticating the identity of the sender of the message.

10

41. The computer program of claim 37, comprising computer executable instructions for identifying a set of services to which the message is addressed.

42. The computer program of claim 37, comprising computer executable instructions for determining whether the sender is authorised to access at least one service; and,

15

in dependence on the result of said authorisation determination, sending the converted message to the identified service.

20

43. The computer program of claim 37, comprising computer executable instructions for searching for data identifying the status of a transaction by reference to a detected transaction identifier.

25

44. A computer system for routing messages to one or more services, comprising:  
means for parsing a message received from a sender;  
means for parsing including means for converting the message into an internal format comprising an attribute part and a data part, said attribute part containing data extracted from received message; and

means for routing the converted message in dependence on the data in the attribute part.

30

45. A computer network comprising at least one computer system connectable to at least one further computer system via a network, the at least one computer system comprising:

DYC Ref: P009272US  
SUN Ref: P5052

31

a parser for converting a message received from a sender into an internal format comprising an attribute part and a data part, said attribute part containing data extracted from the received message; and

5 a router for routing the converted message in dependence on the data in said attribute part.

0934134-082103